



L'ISOLANTE K-FLEX

QUALITY SYSTEM
UNI EN ISO 9001:2000
CERTIFIED BY CERTIQUALITY

www.kflex.com

K-FLEX EC

IZOLATORI OD ELASTOMERA

- GREJANJE I VENTILACIJA
- VODOVOD
- KLIMATIZACIJA

$\mu \geq 3000$

Ispitano po: DIN 1988 / 7

Ne sadrži HCFC - CFC, Cd

Class 1 BS 476 PT 7 1997



K-FLEX EC

Cevi: dužina 2 m



debljina

6-9-13-15-19-25-30-40-50-55-60 mm

prečnik

od 6 do 168 mm

K-FLEX ST

Rolne: 1000 mm širine

Rolne: 1500 mm širine

| STANDARDNE | | SAMOLEPLJIVE NET* | |
|-------------|-------------|-------------------|-------------|
| Debljina mm | Debljina mm | Debljina mm | Debljina mm |
| 6 | 6 | 6 | 6 |
| 10 | 10 | 10 | 10 |
| 13 | 13 | 13 | 13 |
| 16 | 16 | 16 | 16 |
| 19 | 19 | 19 | 19 |
| 25 | 25 | 25 | 25 |
| 32 | 32 | 32 | 32 |
| 40 | 40 | 40 | 40 |
| 50 | 50 | 50 | 50 |



Ploče: 2 m x 1 m za sve debljine

* NET= ojačana mreža

Zaštita:
- ALU
- AL CLAD
- COLOR

PLOČE I ROLNE SA I BEZ
SAMOLEPLJIVOG SLOJA
K-FLEX ST



TEHNIČKI PODACI

| | |
|---|----------------------------|
| Temperaturni opseg | +105 °C |
| Termo-provodljivost λ , W/(m·K) L10 EN ISO 8497 (DIN 52613) | +40 °C = 0,040* |
| Rizik od korozije | DIN 1988/7*; pH neutral |
| Propustljivost μ EN 12086 (DIN 52615) | ≥ 3000 |
| Vatra | Class "1" BS 476 PT 7 1997 |

* Kontrolisano od strane nezavisnog instituta.

L'ISOLANTE K-FLEX zadržava pravo da izmeni podatke i tehničke zahteve bez najave.